

Questions (Q) & Guidance (G):

Choose the Model

Q: Is your customer going to connect to an Ethernet network?

G: If yes, choose the network, "n," model.

Infoprint 1512 base – 30 ppm 600 & 1200 dpi, 1200 & 2400 IQ 32MB/ 366 MHz Parallel and USB Attachments Machine Type 4535-001 Part # 39V0431 Infoprint 1512 network – 30 ppm 600 & 1200 dpi, 1200 & 2400 IQ 32MB/366 MHz USB, Parallel, & Fast Ethernet Attachments

Machine Type 4535-n01

Part # 39V0432

External Attachments Options

Q: Is your customer going to connect to a different network (Token Ring or wireless Ethernet), or might they want an external Ethernet adapter instead of an internal one?

- **G:** Choose from these optional adapters.
- **G:** These are all external adapters, the 1512 does not have any internal connectivity options.
- **G:** All of these adapters connect to the printer's parallel port with the exception of the 802.11g Wireless adapters.

The 802.11g Wireless to USB connects to the USB port and the 802.11g Wireless to Ethernet adapter connects to the Ethernet port.

Token Ring – 3 port PN: 28P1836


| Ethernet 10/100 | BaseTX – 1 port PN: 28P1839 | Ethernet 10/100 | BaseTX – 3 port PN: 28P1840 | PN: 75P6854 | PN: 75P6857

Note: The 3-port adapters offer 2 parallel and 1 serial interface for connecting to the printer. The 1-port adapters only offer a parallel interface.

3 Cables for Local Attachments

Q: Is your customer going to use a local attachment (Parallel or USB) to connect their printer to a computer?

- **G:** They may need one of these cables to attach their printer.
- **G:** Remember, the base model printers come with a parallel and USB adapter while the network models come with USB, Parallel, and Ethernet.



Memory - SDRAM and Flash

Q: Is your customer going to be printing complex jobs (lot of graphics / images), or are they going to be running applications that will require fonts to be downloaded?

- **G:** For complex jobs, the customer should purchase some additional SDRAM memory. The printer can be configured with as much as 160MB (base and network models). The 1512 has one slot for memory DIMM's and one slot for Flash memory.
- **G:** To store fonts or other resources on the printer the customer should purchase flash memory. Storing fonts on the printer improves performance because the fonts will not have to be downloaded from the host for use on the printer with each new print job.

32MB SDRAM PN: 53P7603 PN: 53P7605 PN: 53P7605

Flash Memory Options 32MB Flash PN: 75P4691



Note:

Please see the last page for a specification overview of the Infoprint 1512.

Infoprint 1512 Configuration Guide



5

Paper Handling Input Options

Q: Does your customer need additional input capacity or paper tray covers?

G: The 1512 comes standard with a 250 sheet input drawer and a 1-sheet multipurpose feeder (MPF).

G: The 1512 may be upgraded with one additional 550-sheet paper drawer.

G: Drawer one and the MPF can feed regular paper, envelopes, transparencies, paper labels, or cardstock. The optional paper drawer supports regular paper only.

G: There are no OUTPUT options for the 1512 and there is no DUPLEX feature. Manual duplex is supported with this printer.

550-Sheet 2nd Drawer PN: 39V0514

6

Paper Handling Output Options

G: The Infoprint 1512 does not have any paper output options.

7

MFP Options

G: The Infoprint 1512 does not have any MFP options.

Maintenance ServicePacs

Q: Is your customer interested in upgrading their warranty or buying an extended service agreement?

G: Select one of the offerings in the following table.

G: The Infoprint 1512 comes with a one year depot exchange warranty.

Machine Type	ServicepePac Type	Description	Part Number
4535	ServicePac IN WARRANTY	2 Yr. EasyServ 5x9ND	41W9525
4535	ServicePac IN WARRANTY	3 Yr. EasyServ 5x9ND	41W9526
4535	ServicePac IN WARRANTY	1 Yr. IOR 5x9 ND	41W9527
4535	ServicePac IN WARRANTY	3 Yr. IOR 5x9 ND	41W9529
4535	ServicePac IN WARRANTY	1 Yr. IOR 24x7SD	41W9530
4535	ServicePac IN WARRANTY	3 Yr. IOR 24x7 SD	41W9532
4535	Post-Warranty ServicePacs	2 Year EZS 9x5ND	41W9533
4535	Post-Warranty ServicePacs	2 Year IOR 9x5 ND	41W9534
4535	Post-Warranty ServicePacs	2 Year IOR 24x7 SD	41W9536

9

Infoprint 1512 Supplies

- Q: Would your customer like to purchase some supplies at the same time as they are purchasing their printer?
- **G**: Select one of the offerings in the following table.
- **G:** The Infoprint 1512 base printer ships with a 1,500 page yield toner cartridge; network ships with 2,500 page yield use and return toner cartridge.
- **G:** The best value for the customer is the 6,000 page high yield use and return toner cartridge.
- G: The page count for the cartridge (yield) is based upon 5% cover per page.

Description	Part Number
2,500 page low yield toner cartridge	75P5708
2,500 page low yield use and return toner cartridge	75P5709
6,000 page high yield toner cartridge	75P5710
6,000 page high yield use and return toner cartridge	75P5711
Photoconductor kit, 30,000 yield	75P5712



Infoprint 1512 Specification Overview

Feature	Infoprint 1512 base and network	
Speed	30 ppm letter / 28 ppm A4	
FPOT	As fast as 8 sec	
Maximum Usage	15,000 prints / month	
Resolution	600dpi, 1200IQ, 2400IQ, 1200dpi (@ ½ speed)	
Memory (Std / Max)	32 Mb / 160 Mb (base and network are same)	
Processor	366 MHz, Lawrin IIb ASIC	
Duplex	Manual Duplex Only	
Paper Input (Std / Max)	250 + 1 / 801	
Paper Output (Std / Max)	150 / 150	
Standard Datastreams	Postscript 3, PCL6, PPDS	
MFP Option(s)	No MFP Options for this printer	
Paper Input / Handling Options	Up to one 550 sheet drawer	
Paper Sizes Supported	A4, A5, JIS B5, Letter, Legal, Executive, Folio, 7¾ Envelope, 9 Envelope, 10 Envelope, DL Envelope, C5 Envelope, B5 Envelope	
Media Types Supported	Paper, Cardstock, Transparencies, Some Paper Labels, Envelopes	
Media Weights Supported	Input Tray: 60-90 gsm (16-24 lb.)	
Application Solutions	None	
Standard Attachments	USB, Parallel (+ Ethernet on n model)	
Optional Attachments	Serial, Ethernet, Token Ring, Wireless Ethernet (802.11b)	
Toner Yield	2.5k and 6k toner cartridges available; 1.5k print cartridge ships with 1512 base and 2.5k print cartridge ships with 1512n	
Photoconductor Yield	30k photoconductor kit; printer ships with a 30k photoconductor	
Toner Saving	10 Levels of Darkness Settings – up to 50% toner savings using toner darkness settings	
Warranty	1 Yr Depot Exchange	
Service Upgrades	See ServicePac offerings	
Dimensions (HxWxD) and	9.8in x 15.6in x 13.9in / 22lb	
Weight	248.9mm x 396.2mm x 353.1mm	